

Solid-state contactor 1-phase 3RF2 AC 51 / 20 A / 40 °C 48-460 V / 4-30 V DC low noise



Product brand name	SIRIUS
Product designation	solid-state contactor
Product type designation	3RF23
Manufacturer's article number	_1 / of the accessories that can be ordered 3RF2900-3PA88 _3 / of the accessories that can be ordered 3RF2900-0EA18 _4 / of the accessories that can be ordered 3RF2920-0GA16 _5 / of the accessories that can be ordered 3RF2920-0FA08
Product designation	_1 / of the accessories that can be ordered terminal cover _3 / of the accessories that can be ordered converter _4 / of the accessories that can be ordered load monitoring _5 / of the accessories that can be ordered load monitoring, basis
General technical data	
Product function	low noise
Power loss [W] / for rated value of the current / at AC / in hot operating state	20 W
Insulation voltage	rated value 600 V

Degree of pollution	3
Protection class IP	IP20
Shock resistance / acc. to IEC 60068-2-27	15g / 11 ms
Vibration resistance / acc. to IEC 60068-2-6	2g
Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	K
Reference code / acc. to DIN EN 81346-2	Q
Reference code / acc. to DIN EN 61346-2	Q

Main circuit

Number of poles / for main current circuit	1
Number of NO contacts / for main contacts	1
Number of NC contacts / for main contacts	0
Operating voltage / at AC - at 50 Hz / rated value - at 60 Hz / rated value	48 ... 460 V 48 ... 460 V
Operating frequency / rated value	50 ... 60 Hz
Operating range relative to the operating voltage / at AC - at 50 Hz - at 60 Hz	40 ... 506 V 40 ... 506 V
Operating current at AC-51 / rated value	20 A
Operating current / minimum	500 mA
Rate of voltage rise / at the thyristor / for main contacts / maximum permissible	1 000 V/μs
Blocking voltage / at the thyristor / for main contacts / maximum permissible	1 200 V
Reverse current / of the thyristor	25 mA
Derating temperature	40 °C
Surge current resistance / rated value	600 A
I ² t value / maximum	1 800 A ² ·s

Control circuit/ Control

Type of voltage / of the control supply voltage	DC
Control supply voltage / 1 - at DC / rated value - at DC	30 V 4 ... 24 V
Control supply voltage - at DC / initial value for signal <1> detection - at DC / Full-scale value for signal <0> recognition	4 V 1 V
Control current / at minimum control supply voltage at DC	18 mA
Control current / at DC / rated value	20 mA

Switch-on delay time	1 ms; additionally max. one half-wave
Off-delay time	1 ms; additionally max. one half-wave
Number of NC contacts / for auxiliary contacts	0
Number of NO contacts / for auxiliary contacts	0
Number of CO contacts / for auxiliary contacts	0

Installation/ mounting/ dimensions

Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail
• Side-by-side mounting	Yes
Height	100 mm
Width	22.5 mm
Depth	123.5 mm; 140.5 mm up to product revision E05
Installation altitude / at height above sea level / maximum	1 000 m

Connections/ Terminals

Type of connectable conductor cross-sections	
• for main contacts	
— solid	2x (1.5 ... 2.5 mm ²), 2x (2.5 ... 6 mm ²)
— finely stranded / with core end processing	2x (1 ... 2.5 mm ²), 2x (2.5 ... 6 mm ²), 1x 10 mm ²
• at AWG conductors / for main contacts	2x (14 ... 10)
Type of connectable conductor cross-sections	
• for auxiliary and control contacts	
— solid	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)
— finely stranded / with core end processing	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)
— finely stranded / without core end processing	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)
• at AWG conductors / for auxiliary and control contacts	1x (AWG 20 ... 12)
Tightening torque	
• for main contacts / with screw-type terminals	2 ... 2.5 N·m
• for auxiliary and control contacts / with screw-type terminals	0.5 ... 0.6 N·m
Tightening torque [lbf·in]	
• for main contacts / with screw-type terminals	18 ... 22 lbf·in
• for auxiliary and control contacts / with screw-type terminals	4.5 ... 5.3 lbf·in
Design of the thread / of the connection screw	
• for main contacts	M4
• of the auxiliary and control contacts	M3
Wire stripping length / of the cable	
• for main contacts	7 mm
• for auxiliary and control contacts	7 mm

Ambient conditions

Ambient temperature	
- during operation - during storage	-25 ... +60 °C -55 ... +80 °C
Electromagnetic compatibility	
Conducted interference	
due to burst / acc. to IEC 61000-4-4	2 kV / 5 kHz behavior criterion 2
due to conductor-earth surge / acc. to IEC 61000-4-5	2 kV behavior criterion 2
due to conductor-conductor surge / acc. to IEC 61000-4-5	1 kV behavior criterion 2
due to high-frequency radiation / acc. to IEC 61000-4-6	140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1
Electrostatic discharge / acc. to IEC 61000-4-2	4 kV contact discharging / 8 kV air discharging, behavior criterion 2
Conducted HF-interference emissions / acc. to CISPR11	Class A for industrial sector, class B for the domestic, business and commercial environments up to 16 A, AC51 low noise
Field-bound HF-interference emission / acc. to CISPR11	Class A for industrial sector, class B for the domestic, business and commercial environments up to 16 A, AC51 low noise
Short-circuit protection, design of the fuse link	
Manufacturer's article number	
of gS fuse for semiconductor protection / at NH design	3NE1814-0
of full range R fuse link for semiconductor protection / at cylindrical design	5SE1325
of back-up R fuse link for semiconductor protection / at NH design	3NE8015-1
of back-up R fuse link for semiconductor protection / at cylindrical design 10 x 38 mm	3NC1032
of back-up R fuse link for semiconductor protection / at cylindrical design 14 x 51 mm	3NC1450
of back-up R fuse link for semiconductor protection / at cylindrical design 22 x 58 mm	3NC2263
Manufacturer's article number / of the gG fuse	
at NH design	3NA6807
at cylindrical design 10 x 38 mm	3NW6005-1; These fuses have a smaller rated current than the semiconductor relays
at cylindrical design 14 x 51 mm	3NW6105-1; These fuses have a smaller rated current than the semiconductor relays
at cylindrical design 22 x 58 mm	3NW6205-1; These fuses have a smaller rated current than the semiconductor relays
Manufacturer's article number	
of DIAZED fuse	5SB171
of NEOZED fuse	5SE2320
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RF2320-1CA44>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RF2320-1CA44>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RF2320-1CA44>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RF2320-1CA44&lang=en





